

M 715 1 ¼ ton-Kaiser Jeep



V r.1965 navrhl a vyvinul Kaiser Jeep tento model-seriový náklad'áček,často nazývaný „Fivequarter“-pětičtvrťka.Tento typ byl vybrán místo dosud sloužící Dodge M37 a bylo dodáno do armády v letech 1967-1969 přes 33.000 vozidel čtyř modelů včetně ambulance,které měly stejné podvozky,ale jiné nástavby. Původně tento jeep byl civilní „Gladiátor“,posléze modifikován pro vojenské účely.



Plátěná střecha byla používána až po vojenské úpravě vozidla

**Specifikace-Motor-řadový 6V Jeep 230Ci OHC Tornado-140 Hp
toč.moment 210Lb-Ft při 1.750 Rpm
rychlostní skříň-T98a 6.32:1(bába)-nízkopřevodní
redukční skříň NP 200 2-mízkopřevodní
přední diferenciál Dana 66-zadní Dana 70(plněplovoucí) převod 38:1
uzávěrky diferenciálu**



M 715-kabina vozu

TRUCK, CARGO
 1 1/4 TON, 4 X 4, M-715, W/WN
 FED. STOCK NO. 2320-921-6366
 MFD. BY KAISER JEEP CORPORATION TOLEDO, OHIO
 MFR. MODEL 3521 MFR. SER. NO. [REDACTED]
 MFR. PART NO. 1000545 DATE DEL. [REDACTED]
 CONT. No. DA-20-113-AMC-10235(T)(MYP)
 U.S. PROPERTY INSPECTED



SERVICING DATA, TRUCK, 1 1/4 TON, 4X4, ELECTRICAL SYSTEM 24V.
GASOLINE OCTANE NO. MIN. 68

GASOLINE TANK CAPACITY 28 GALS
 COOLING SYSTEM CAPACITY 12 QTS.
 CRANKCASE CAP 5 QTS. + 1 QT. FOR FILTER

TEMP.	ENG. OIL	GEAR OIL	GREASE
ABOVE 32°F.	OE-30	GO-90	GAA
40°F. TO -10°F.	OE-10W	GO-90	GAA
0°F. TO -59°F.	OES	GO5	GAA

TIRE INFLATION PRESSURES

	HIGHWAY & CROSS-COUNTRY	MUD, SAND & SNOW NOTE: MAXIMUM SUSTAINED SPEED 5 M.P.H.
FRONT	25	10 P.S.I.
REAR	45	15 P.S.I.

CAUTION
 MAXIMUM PERMISSIBLE ROAD SPEEDS
 IN THE FOLLOWING GEAR POSITIONS

TRANSMISSION	TRANSFER CASE IN	
	HIGH RANGE	LOW RANGE
IN		
4	60 M.P.H.	35 M.P.H.
3	40	21
2	22	11
1	11	5
REVERSE	9	4

TO DRAIN COOLING SYSTEM OPEN RADIATOR COCK LOCATED ON BOTTOM OF RADIATOR ON RIGHT SIDE AND CYL. BLOCK DRAIN PLUG ON LEFT SIDE OF ENGINE NEXT TO STARTER.

WEIGHT AND DIMENSION DATA FOR TRUCK, CARGO, 1 1/4 TON, 4 X 4, M-715

	A	B	C	D	E
W/WINCH	56.6	80.4	33"	41	320.75
WO/WINCH	60.7	84.4	45"	30	299.75

WEIGHTS
 W/O CREW EMPTY CROSS COUNTRY HIGHWAY

PAYLOAD	EMPTY	CROSS COUNTRY	HIGHWAY
FRONT AXLE*	2800	2500	3000
REAR AXLE	2700	2800	2800
TOTAL LBS. *	5500	5200	5700
* WITH WINCH ADD 500 LBS.			
MAX. TOWED LOAD (PINTLE TOWED)	4200		4450

SHIPPING CUBAGE CU. FT.
 W/WINCH 640
 WO/WINCH 606

75.5 OVERALL REDUCIBLE TO 59

